



Roller speargun with rubbers *Extreme 1.5 90* (Big Hawk)



User & Maintenance Manual

CAUTION

Please before using the speargun you must read this instruction manual throughly, paying close attention to everything that concerns the security of yourself and people around you. Store it for further future reference.

INTRODUCTION

CONGRATULATIONS. You have just chosen the most technologically advanced and reliable speargun on the market. Extreme1 is the final result of years of studies and tests. Precision, maneuverability and reliability are the main features of the project.

CAUTION

Read the instructions in this manual carefully as they are essential for your safety and moreover to ensure the longevity of your speargun. Diving equipment should be used only by properly trained people. To guarantee the maximum safety, maintenance of your equipment should be provided only by an authorized Sea Hawk Sub center.

CAUTION

Please read this instruction manual before use, and keep it, paying close attention to everything that concerns the security.

CAUTION

Don't leave the speargun loaded and unattended neither on the ground nor on a boat, use it solely for spearfishing!

CAUTION

Never point loaded speargun, even momentarily, against yourself or other diver. Always turn the rod tip away from you and other people around. At the end of the hunting unload the speargun.

CAUTION

In Italy, in accordance with art. 18 of Law 963/65 the use of spearguns is permitted only to guests over 16 years. Inquire about the applicable laws for the use of the rifle by children in other countries.

PRECAUTIONS

Before using the gun, always check the following:

- Check the proper operation of the firing system,
- Check the tightening of the screws.
- Ensure that the knots are secure.
- Check that bands are in good condition, in particular make sure that for cracks, damage, cracks and pulling away from the ends. In that case, do not hesitate to replace them.

Do not leave the gun to direct sunlight or source of heat.

- After each use, rinse with plenty of fresh water gun.

PRODUCT DESCRIPTION

Light, fluid movements from the powerful shot, clean and precise, the Extreme 1.5-90 was created to satisfy the needs of specific fishing. The Extreme1.5-90 is a monoroller elastic roller from 17.5mm, additional elastic of 16mm and arrow-rod from 7-7.5. Suitable for fishing in the Ocean and deep fishing, where you need a lot of power. Its ease the load makes it even more pleasant to use. Thanks to its particular structure with a double wing profile with mechanical sunken releases a perception of a weapon even shorter. Ideal for the ambush and precise in appearance. The Extreme 1.5-90 turns out to be a good compromise between power and ease.

WINDING OF SAGOLA

Canal YouTube SeaHawkSub is the video explaining the proper winding of the line.

Line release AUTOMATIC

Inserting the rod into its seat in the active block line-releaser. Pressing the trigger rod it is expelled and is automatically unlocked line-releaser.

LOADING

The Sea Hawk Sub Spearguns using an innovative and unique that allows for convenient upload action in perfect safety.

Before loading check that the shaft is engaged, the line releasing blocked and nylon wrapped along the stem properly.

Step1: Block to load the first notch on the underside, turn the gun grabbing and pulling the straps on the last notch of the shaft closer to the trigger. (Attention at this time the gun is already partially loaded)

Step2: Insert the pin into the hole of steel ways to load a handle and pull up to.

Notch desired. When the bands are new it is recommended to load the penultimate notch for at least 2-3 exit at sea.

Step3: Afferrare l'elastico da 16 aggiuntivo, se necessario agganciandolo temporaneamente al pretensionatore sull'ala sinistra. Posizionare il fucile sullo sterno e caricarlo fino alla tacca desiderata.

ADDITIONAL INFO

The Sea Hawk Sub rifles are finished and assembled by hand with so many hours of work. Though apparently all the same each piece is unique.

The mimentismo is made at the time and on commission without a specific pattern.

CARATTERISTICHE TECNICHE

Length without rod: 1123 mm

Rod length: 1,263 mm

Widest point on the stem: 126 mm

Wood: Mahogany laminated strips 6

Weight: about 2.3kg

Auction: 7-7.5 x 120

Elastic: Ø17.5 with additional 16

Trigger: Sub Sea Hawk backlog

Bridge: Steel;

Pulleys: Delrin roller;

Frame color: Camouflage Mahogany spots of various colors with silver logo;

Handle color: Black with seizure microspheres

Resinatura: 3 hands of two component epoxy resin;

Paint: 3 coats of two-component polyurethane;

Lanyard: Nylon 1.2mm

Carichino: Round Stainless Steel 6 / 7mm (pin type portapesci)